

Load Baseline

Tyler Jones, UC Berkeley

- Goal: To establish a load baseline profile prediction for demand response event that is accurate, functional, and generates quick results.



SIEMENS



RECOVERY.GOV

Factors Affecting SDH Building Loads

- HVAC
 - Occupancy
 - Outside Air Temperature
 - Radiant Effects
 - Relative Humidity
- Plug Loads
 - Occupancy
 - Academic Calendar
- Lighting
 - Occupancy
 - Time of Year (Radiant effects)



SIEMENS



RECOVERY.GOV

Data Sets for Determining Baseline Load Profile

- To determine an accurate Baseline Load Profile, a method in which the set of data needed to predict the load was used:
 - Actual Load at 10 AM ($a(d,10)$)
 - Actual Load at 11 AM ($a(d,11)$)
 - Average Load of 3 hottest days of previous 10 days
 - Average Load of 3 hottest days of same 10 day period one year ago
 - Occupancy (no dynamic data available yet)



SIEMENS



iTRIS
Center for Information Technology Research in the Interest of Society



RECOVERY.GOV

Data Restrictions

- Days of elevated conditions are desired to run the data given the project goal.
- “Static” occupancy data (employment numbers for the time of year) available. Dynamic occupancy data is obtainable, but requires the use of motion sensors, or access to card reader data, or a survey of occupants.
- Trend data is only trended back so far due to the newness of the building.



SIEMENS



RECOVERY.GOV

Methods to Determining Baseline Load Profile

- Using a Morning Correction factor with the loads measured the morning of DR event.
- Using an Occupation Correction factor with the averages of the hottest three loads measured from last year (this month), taking into account, occupancy differences.
- Using an HVAC Correction factor for HVAC efficiency.



SIEMENS



RECOVERY.GOV

Morning Correction Factor

- Method used for Morning Correction factor is derived from LBNL's Best Method. The correction factor is as follows:

$$c(d) = \frac{al(d, h = 10) + al(d, h = 11)}{pl(d, h = 10) + pl(d, h = 11)}$$

$al(d, h)$ – the actual load for the day and the hour

$pl(d, h)$ – the average of the 3 highest actual loads at this hour over the 10 previous days.



SIEMENS



RECOVERY.GOV

Previous Year Correction Factors

- The previous year, functions as a safeguard for situations where there are not elevated temperatures for 10 days prior to a demand response day.
- The efficiency of HVAC systems will deteriorate by a small amount over a year. There is code, for implementation, to correct for changes in the HVAC system. The changes that will be determined are the kW/ton rating and COP.
- The occupancy will change with each year or season raising the need for Occupancy Correction Factor.



SIEMENS



RECOVERY.GOV

Occupancy Correction Factor

- A preliminary Occupancy Correction Factor was used for calculating baseline load.



SIEMENS



RECOVERY.GOV

HVAC Correction Factor

For electric (Centrifugal) system:

$$\text{Net refrigeration capacity (TR)} = \frac{m c_p (T_{in} - T_{out})}{3024}$$

$$\text{Power (kW)} = \sqrt{3} \times V \times I \times \cos\phi$$

$$\text{kW/ton rating} = \frac{\text{Measured compressor power (kW)}}{\text{Net refrigeration capacity (TR)}}$$

Where:

m : mass flow rate of chilled water, kg/hr

C_p : Specific heat, kcal/kg °C

T_{in} : Chilled water temperature at evaporator inlet, °C

T_{out}: Chilled water temperature at evaporator outlet, °C

$$\text{COP} = \frac{3.516}{\text{kW/ton}}$$

$$c(\text{COP}) = \frac{\text{COP}_{TY}}{\text{COP}_{LY}}$$

- For steam (absorption) system: There is no correction factor that has been implemented.
- **We can factor this in, once we add additional submeters on HVAC system.**



SIEMENS



RECOVERY.GOV

Test Data

- Data was used from months of October 2010, February 2011, and April 2011. Data was limited due to system setup and outages (September 2010 not available)
- Previous year data from February was used (October 2009 data not available)
- Weather data from sMap
- “Static” Employment/Office Occupancy data used for preliminary Occupancy Correction Factor until further occupancy measurement is possible.



SIEMENS



iTRIS
Center for Information Technology Research in the Interest of Society



RECOVERY.GOV

Time Steps for Prediction

- Due to limited weather data, the time step was limited to 1 hour for preliminary calculations. But with temperature monitoring on sMap server, time steps have been reduced to 5 minutes or less if needed.
- Smaller time steps will allow for greater knowledge of further steps in demand response.



SIEMENS



ITRIS
Center for Information Technology Research in the Interest of Society



RECOVERY.GOV

Results

- Prediction Results tested for October 14 & 15, 2010 with Morning Correction factor*. Algorithm made predictions for these two days and the predictions were compared to the actual data received.
- Prediction Results also tested for February 4, 2011, with Morning Correction Factor, and with a preliminary Occupancy Correction Factor that will be refined with more data.

*other two correction factors not available for time period.







SIEMENS







RECOVERY.GOV



October Results



February Results With and Without Occupancy Correction Factor



April Results



- Results for April 26, 2011 from 12 PM until 6 PM
- Largest region of error is 6% from 2 PM to 3 PM for MSA



Future Work

- A refined Occupancy Correction factor to be developed with more dynamic occupancy data that is to be determined in the coming weeks
- Implementation of HVAC Correction factor with the installation of flow submeters on the Sutardja Dai Hall HVAC system.



SIEMENS



RECOVERY.GOV

Questions

Acknowledgement

This material is based upon work supported by the Department of Energy under Award Number DE-EE0003847

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



SIEMENS



RECOVERY.GOV